



建議孔座：H7
 軸心使用建議
 一般高荷重用：d8
 一般輕荷重用：e7
 高精度使用：f7

產品標示法：SPB-d* \bar{D} *L
 (SPB-內徑*外徑*長度)

Ød	ØD	L																		單位:mm		
		8	10	12	15	16	20	25	30	35	40	45	50	60	70	80	100	120	130		140	150
8 +0.028 +0.018	12 +0.018 +0.007	●	●	●	●																	
10 +0.028 +0.018	14 +0.018 +0.007	●	●	●	●		●															
12 +0.034 +0.016	18 +0.018 +0.007	●	●	●	●	●	●	●														
13 +0.034 +0.016	19 +0.021 +0.008		●	●	●		●															
14 +0.028 +0.018	20 +0.021 +0.008		●	●	●		●	●														
15 +0.028 +0.018	21 +0.021 +0.008		●	●	●	●	●	●														
16 +0.034 +0.016	22 +0.021 +0.008		●	●	●	●	●	●	●													
18 +0.034 +0.016	24 +0.021 +0.008		●	●	●	●	●	●	●	●			●									
20 +0.041 +0.020	28 +0.021 +0.008		●	●	●	●	●	●	●	●	●		●	●								
20 +0.041 +0.020	30 +0.021 +0.008					●	●	●	●	●	●	●	●	●								
25 +0.041 +0.020	33 +0.025 +0.009			●	●	●	●	●	●	●	●	●	●	●	●							
25 +0.041 +0.020	35 +0.025 +0.009			●	●	●	●	●	●	●	●	●	●	●	●							
30 +0.041 +0.020	38 +0.025 +0.009			●	●		●	●	●	●	●	●	●	●	●							
30 +0.041 +0.020	40 +0.025 +0.009			●	●		●	●	●	●	●	●	●	●	●							
31.5 +0.050 +0.025	40 +0.025 +0.009						●	●	●	●	●	●	●	●	●							
35 +0.050 +0.025	44 +0.025 +0.009						●	●	●	●	●	●	●	●	●							
35 +0.050 +0.025	45 +0.025 +0.009						●	●	●	●	●	●	●	●	●							
40 +0.050 +0.025	50 +0.025 +0.009				●		●	●	●	●	●	●	●	●	●	●						
40 +0.050 +0.025	55 +0.030 +0.011				●		●	●	●	●	●	●	●	●	●	●						
45 +0.050 +0.025	55 +0.030 +0.011						●	●	●	●	●	●	●	●	●	●						
45 +0.050 +0.025	56 +0.030 +0.011							●	●	●	●	●	●	●	●	●						
45 +0.050 +0.025	60 +0.030 +0.011								●	●	●	●	●	●	●	●						
50 +0.050 +0.025	60 +0.030 +0.011								●	●	●	●	●	●	●	●						
50 +0.050 +0.025	62 +0.030 +0.011									●	●	●	●	●	●	●						
50 +0.050 +0.025	65 +0.030 +0.011										●	●	●	●	●	●						
55 +0.060 +0.030	70 +0.030 +0.011											●	●	●	●	●	●					
60 +0.060 +0.030	74 +0.030 +0.011												●	●	●	●	●	●				
60 +0.060 +0.030	75 +0.030 +0.011													●	●	●	●	●	●			
63 +0.060 +0.030	76 +0.030 +0.011														●	●	●	●	●			
65 +0.060 +0.030	80 +0.030 +0.011															●	●	●	●	●		
70 +0.060 +0.030	85 +0.035 +0.013																●	●	●	●	●	
70 +0.060 +0.030	90 +0.035 +0.013																	●	●	●	●	●
75 +0.060 +0.030	90 +0.035 +0.013																		●	●	●	●
75 +0.060 +0.030	95 +0.035 +0.013																			●	●	●
80 +0.060 +0.030	96 +0.035 +0.013																				●	●
80 +0.060 +0.030	100 +0.035 +0.013																					●
90 +0.071 +0.026	110 +0.035 +0.013																					
100 +0.071 +0.026	120 +0.035 +0.013																					
110 +0.071 +0.026	130 +0.040 +0.015																					
120 +0.071 +0.026	140 +0.040 +0.015																					
125 +0.083 +0.043	145 +0.040 +0.015																					
130 +0.083 +0.043	150 +0.040 +0.015																					
140 +0.083 +0.043	160 +0.040 +0.015																					
150 +0.083 +0.043	170 +0.040 +0.015																					
160 +0.083 +0.043	180 +0.040 +0.015																					



建議孔座：H7
 軸心使用建議
 一般高荷重用：d8
 一般輕荷重用：e7
 高精度使用：f7

產品標示法：SPF-dxL
 (SPF- 內徑 X含凸緣長度)

Ød	ØD	φF	t ⁰ _{-0.1}	單												
				L 位 mm -0.1 -0.3												
				10	15	20	25	30	35	40	50	60	67.5	80	100	
10	+0.040 +0.025	14	+0.034 +0.023	22	2	1010	1015	1020								
12	+0.050 +0.032	18	+0.034 +0.023	25	3	1210	1215	1220	1225	1230						
13	+0.050 +0.032	19	+0.041 +0.028	26	3	1310	1315	1320								
14	+0.050 +0.032	20	+0.041 +0.028	27	3		1415	1420	1425							
15	+0.050 +0.032	21	+0.041 +0.028	28	3	1510	1515	1520	1525	1530						
16	+0.050 +0.032	22	+0.041 +0.028	29	3		1615	1620	1625	1630	1635	1640				
20	+0.061 +0.040	30	+0.041 +0.028	40	5		2015	2020	2025	2030	2035	2040				
25	+0.061 +0.040	35	+0.050 +0.034	45	5		2515	2520	2525	2530	2535	2540	2550			
30	+0.061 +0.040	40 440	+0.050 +0.034	50	5			3020	3025	3030	3035	3040	3050			
31.5	+0.075 +0.050	40	+0.050 +0.034	50	5			3120		3130	3135	3140				
35	+0.075 +0.050	45	+0.050 +0.034	60	5			3520	3525	3530	3535	3540	3550			
40	+0.075 +0.050	50	+0.050 +0.034	65	5			4020	4025	4030	4035	4040	4050			
45	+0.075 +0.050	55	+0.060 +0.041	70	5					4530	4535	4540	4550	4560		
50	+0.075 +0.050	60	+0.060 +0.041	75	5					5030	5035	5040	5050	5060		
55	+0.090 +0.060	65	+0.060 +0.041	80	5							5540	5560			
60	+0.090 +0.060	75	+0.062 +0.043	90	7.5							6040	6050	6060	6080	
63	+0.090 +0.060	75	+0.060 +0.043	85	7.5									6367		
70	+0.090 +0.060	85	+0.073 +0.051	105	7.5								7050		7080	
75	+0.090 +0.060	90	+0.073 +0.051	110	7.5									7560		
80	+0.090 +0.060	100	+0.073 +0.051	120	10									8060	8080	80100
90	+0.107 +0.072	110	+0.076 +0.054	130	10									9060	9080	
100	+0.107 +0.072	120	+0.076 +0.054	150	10										10080	100100
120	+0.107 +0.072	140	+0.068 +0.063	170	10										12080	120100